

SET-UP SHEET

XRAY XB8'22 SET-UP VER.01 ©XRAY

XRAY XB8'22 PIVOT BALL

RACE	MUGEN CUP		
TRACK	Futaba Buggy Tract		
NAME	Nana Kaiho	DATE	30th Oct 2024

TEMPERATURE AIR	28°C	TEMPERATURE TRACK	30°C
LAPS	41.3	FINAL POSITION	2
BEST LAP TIME	40.3 /sec	RACE LENGTH	/min

TRACKS			
SIZE	☐ OPEN	☒ MEDIUM	☐ TIGHT
TRACTION	☐ LOW	☒ MEDIUM	☐ HIGH
SURFACE	☐ SMOOTH	☒ MEDIUM	☐ BUMPY
TYPE	☐ HARD PACKED	☒ SOFT DIRT	☐ CLAY
	☐ BLUE GROVE	☐ ASTRO TURF	☐ GRASS
CONDITION	☐ DRY	☒ DUSTY	☐ WET
			☐ MUD

DIFFERENTIAL			
CASE MATERIAL	FRONT	CENTER	REAR
OIL	7K	7K	3K
CROWN GEAR			

GEARING	
CLUTCH SHOE	3 ☐ 4 ☐
SPRINGS	
CLUTCH BELL	/T
SPUR GEAR	/T

SHOCKS																									
FRONT	REAR																								
3dots	3dots																								
550 /St	500 /St																								
<table border="1"> <tr> <th colspan="4">STANDARD PISTONS</th> </tr> <tr> <td>☒ 6 HOLES</td> <td>☐ 1.1 mm</td> <td>☐ 6 HOLES</td> <td>☒</td> </tr> <tr> <td>☐ 8 HOLES</td> <td>☒ 1.2 mm</td> <td>☐ 8 HOLES</td> <td>☒</td> </tr> <tr> <td>☐ 10 HOLES</td> <td>☐ 1.3 mm</td> <td>☒ 10 HOLES</td> <td>☐</td> </tr> <tr> <td></td> <td>☐ 1.4 mm</td> <td></td> <td></td> </tr> <tr> <td colspan="4">OTHER</td> </tr> </table>		STANDARD PISTONS				☒ 6 HOLES	☐ 1.1 mm	☐ 6 HOLES	☒	☐ 8 HOLES	☒ 1.2 mm	☐ 8 HOLES	☒	☐ 10 HOLES	☐ 1.3 mm	☒ 10 HOLES	☐		☐ 1.4 mm			OTHER			
STANDARD PISTONS																									
☒ 6 HOLES	☐ 1.1 mm	☐ 6 HOLES	☒																						
☐ 8 HOLES	☒ 1.2 mm	☐ 8 HOLES	☒																						
☐ 10 HOLES	☐ 1.3 mm	☒ 10 HOLES	☐																						
	☐ 1.4 mm																								
OTHER																									
<table border="1"> <tr> <th colspan="4">VALVE PISTONS</th> </tr> <tr> <td>☐ 5+2 HOLES</td> <td>☐ 1.5 mm</td> <td>☐ 5+2 HOLES</td> <td>☐</td> </tr> <tr> <td>☐ 6+2 HOLES</td> <td>☐ 1.3 mm</td> <td>☐ 6+2 HOLES</td> <td>☐</td> </tr> <tr> <td>☐ 8+2 HOLES</td> <td>☐ 1.4 mm</td> <td>☐ 8+2 HOLES</td> <td>☐</td> </tr> <tr> <td></td> <td>☐ 1.2 mm</td> <td></td> <td></td> </tr> <tr> <td></td> <td>☐ 1.3 mm</td> <td></td> <td></td> </tr> </table>		VALVE PISTONS				☐ 5+2 HOLES	☐ 1.5 mm	☐ 5+2 HOLES	☐	☐ 6+2 HOLES	☐ 1.3 mm	☐ 6+2 HOLES	☐	☐ 8+2 HOLES	☐ 1.4 mm	☐ 8+2 HOLES	☐		☐ 1.2 mm				☐ 1.3 mm		
VALVE PISTONS																									
☐ 5+2 HOLES	☐ 1.5 mm	☐ 5+2 HOLES	☐																						
☐ 6+2 HOLES	☐ 1.3 mm	☐ 6+2 HOLES	☐																						
☐ 8+2 HOLES	☐ 1.4 mm	☐ 8+2 HOLES	☐																						
	☐ 1.2 mm																								
	☐ 1.3 mm																								

ANTI-ROLL BAR	
FRONT	REAR
2.3 /mm	2.6 /mm
THICKNESS	

TIRES	
FRONT	REAR
Slide-Lock	Slide-Lock
S4	S4
MUGEN	MUGEN
WHEELS	

ENGINE	
TYPE	O.S.Speed ONG
MUFFLER	O.S.Speed
MANIFOLD	O.S.Speed 75
PLUG	O.S.Speed P3
FUEL	KLOTZ 25

BODY	
EASY	EASY LIGHT
☒	☐
TOTAL WEIGHT	
/g	

