

SET-UP SHEET

XRAY XB8'22 SET-UP VER.01 ©XRAY

XRAY XB8'22 PIVOT BALL

RACE	Japanese National		
TRACK	Futaba Buggy Tract		
NAME	Nana Kaiho	DATE	9th Oct 2022
TEMPERATURE AIR	20°C	TEMPERATURE TRACK	25°C
LAPS	6	BEST LAP TIME	40.3 /sec
FINAL POSITION		RACE LENGTH	/min
TRACKS			
SIZE	<input type="checkbox"/> OPEN	<input checked="" type="checkbox"/> MEDIUM	<input type="checkbox"/> TIGHT
TRACTION	<input type="checkbox"/> LOW	<input type="checkbox"/> MEDIUM	<input checked="" type="checkbox"/> HIGH
SURFACE	<input checked="" type="checkbox"/> SMOOTH	<input type="checkbox"/> MEDIUM	<input type="checkbox"/> BUMPY
TYPE	<input type="checkbox"/> HARD PACKED	<input type="checkbox"/> SOFT DIRT	<input checked="" type="checkbox"/> CLAY
	<input type="checkbox"/> BLUE GROVE	<input type="checkbox"/> ASTRO TURF	<input type="checkbox"/> GRASS
CONDITION	<input type="checkbox"/> DRY	<input type="checkbox"/> DUSTY	<input checked="" type="checkbox"/> WET
	<input type="checkbox"/> MUD		
DIFFERENTIAL			
CASE MATERIAL	FRONT	CENTER	REAR
OIL	7K	7K	3K
CROWN GEAR			
GEARING			
CLUTCH SHOE	3		4
SPRINGS			
CLUTCH BELL	13	SPUR GEAR	48
SHOCKS			
FRONT	3dots	TYPE	3dots
		SPRINGS	
		MEMBRANE	
	550 /cst	OIL	500 /cst
STANDARD PISTONS			
<input checked="" type="checkbox"/> 6 HOLES	<input type="checkbox"/> 1.1 mm	<input type="checkbox"/> 6 HOLES	<input checked="" type="checkbox"/>
<input type="checkbox"/> 8 HOLES	<input checked="" type="checkbox"/> 1.2 mm	<input type="checkbox"/> 8 HOLES	<input type="checkbox"/>
<input type="checkbox"/> 10 HOLES	<input type="checkbox"/> 1.3 mm	<input checked="" type="checkbox"/> 10 HOLES	<input type="checkbox"/>
	<input type="checkbox"/> 1.4 mm	<input type="checkbox"/> 10 HOLES	<input type="checkbox"/>
	OTHER		
VALVE PISTONS			
<input checked="" type="checkbox"/> 5+2 HOLES	<input type="checkbox"/> 1.5 mm	<input type="checkbox"/> 5+2 HOLES	<input type="checkbox"/>
<input type="checkbox"/> 6+2 HOLES	<input type="checkbox"/> 1.3 mm	<input checked="" type="checkbox"/> 6+2 HOLES	<input type="checkbox"/>
<input type="checkbox"/> 8+2 HOLES	<input type="checkbox"/> 1.4 mm	<input type="checkbox"/> 8+2 HOLES	<input type="checkbox"/>
	<input type="checkbox"/> 1.2 mm	<input type="checkbox"/> 8+2 HOLES	<input type="checkbox"/>
	<input type="checkbox"/> 1.3 mm		
ANTI-ROLL BAR			
FRONT	2.3 /mm	THICKNESS	2.6 /mm
TIRES			
FRONT	Sliderock	BRAND	Sliderock
	M4	COMPOUND	M4
	MOLD	INSERTS	MOLD
	MUGEN	WHEELS	MUGEN
ENGINE			
TYPE	O.S. SPEED ONG		
MUFFLER	O.S. SPEED		
MANIFOLD	O.S. SPPED 75		
PLUG	O.S. SPEED P3		
FUEL	KLOTZ 25		
BODY			
EASY EASY LIGHT	<input checked="" type="checkbox"/>	OTHER	
TOTAL WEIGHT	3500 /g		

