

RACE		
TRACK	R C マニアックスアリーナ	
NAME	Shoya Yamasaki	DATE

LAPS		BEST LAP TIME	sec
QUALIFYING POSITION		FINAL POSITION	

TRACK	
SIZE	☐ OPEN ☒ MEDIUM ☐ TIGHT
TRACTION	☐ VERY-LOW ☐ MEDIUM ☒ VERY-HIGH
SURFACE	☐ SMOOTH ☐ MEDIUM ☐ BUMPY
TYPE	☐ CLAY ☒ CARPET ☐ ASTRO
CONDITION	☐ BLUE GROOVE ☐ HARD PACKED ☐ DRY
	☐ DUSTY ☐ LOAMY ☐ WET

TRANSMISSION	
DIFFERENTIAL	
BALL DIFF ☐	GEAR DIFF ☐ ACTIVE DIFF ☒
OIL	7000 cst
SATELLITE GEARS	COMPOSITE ☐ STEEL ☐ GEARS 2 ☐ 4
SLIPPER	2 PAD ☐ 3 PAD ☐ ☒ 4 PAD

GEARING	
PINION	32
SPUR GEAR	69

GEAR BOX	
FRONT LCG	☒
REAR LCG	☐

FRONT	SHOCKS	REAR
3dot42mm	SPRINGS	2dot57mm
cst 500	OIL	cst 450
☒ 2 HOLES	PISTONS	☒ 2 HOLES
☐ 3 HOLES	☒ ø1.6mm	☐ 3 HOLES
☐ 6 HOLES	☐ ø1.7mm	☐ 6 HOLES
OTHER	OTHER	OTHER
DOWNSTOP SHIM	1	DOWNSTOP SHIM
LENGTH	23	LENGTH
UPSTOP SHIM	1	UPSTOP SHIM
COLLAR	STANDARD -2mm	COLLAR
OTHER	KIT BALL JOINT	OTHER

FRONT	SHOCK TOWER	REAR
ALU ☐ GRAPHITE ☒		GRAPHITE ☒ ALU ☐

FRONT	ANTI ROLL BAR	REAR
1.1	THICKNESS	1.3

FRONT	TIRES	REAR
	BRAND	
	COMPOUND	
	INSERTS	
	WHEELS	

ELECTRONICS	
MOTOR	G タバ 17.5
MOTOR TIMING	4200
SPEEDO	
BATTERY	

BODY	
	☒ LIGHT

COMMENT	
325241アクスル 324101ダイレクト使用	

FRONT		REAR	
STEERING BLOCK	MEDIUM ☐ HARD ☐ GRAPHITE ☒ ALU ☐	SHIM	1 /mm
LONGER BUSHINGS	UP ☒ DOWN ☐	SHIM	2 /mm
CAMBER LINK LOCATION	2 1	DRIVE SHAFT	Length 75 /mm
CASTER BLOCK	MEDIUM ☐ HARD ☐ GRAPHITE ☒ ALU ☐	SHIM	2.5 /mm
FLAT ARM	3 2 1	SHIM	2 /mm
LSM ARM	2 1	XB2D SUSP ARM	1 2 3
		XB4 SUSP ARM	1 2

FRONT		REAR	
CASTER BUSHINGS	0° ☒ 2.5° ☐ 5° ☐	WING POSITION	YES ☐ NO ☒
KICK-UP °	KIT 26° ☒	BUMP STEER SHIM	2.5 /mm
WING CUTTING LINE / SIDE LINE	1 2 3 4 5	SHOCK POSITION	FRONT ☒ REAR ☐
		WING TYPE	CENTER FIN YES ☐ NO ☐
		WING POSITION	UP ☐ MIDDLE ☒ DOWN ☐

FRONT		REAR	
FRONT TOE	1.5	REAR TOE	IN
OFFSET	/slots	EXTENSION	0 SLOTS ☐ 1 SLOT ☒ 2 SLOTS ☐ 3 SLOTS ☐
WHEELBASE	SHIM 0 /mm	BATTERY PLACEMENT	LONG SIDE FRONT 1 2 3 LONG SIDE REAR 1 2 3
ROLL CENTER	HARD ☒ ALU ☐	BATTERY SIZE	STD. SHORT ☐ LOW SHORT ☐
		UPPER BRACE	YES ☐ NO ☐
		ROLL CENTER	HARD ☐ GRAPHITE ☐ ALU ☒
		GUARD BRACE FLEX	1 2
		SERVO HORNS	SHIM 2 /mm
		SERVO BRACE	YES ☐ NO ☒

FRONT		REAR	
STEERING ARMS	HARD ☒ GRAPHITE ☐ ALU ☐	REAR ROLL CENTER HOLDERS	RF 0.5° ☒ 1° ☐
STEERING PLATE	HARD ☐ GRAPHITE ☐ ALU ☒	SHIMS	mm
		RR 0.5° ☒ 1° ☐	

FRONT		REAR	
FRONT CAMBER	1	DIFF HEIGHT	2
FRONT ARM	MEDIUM ☐ HARD ☐ GRAPHITE ☒	REAR CAMBER	
		REAR ARM	MEDIUM ☐ HARD ☐ GRAPHITE ☒
		RISE HEIGHT	15 /mm
		RISE HEIGHT	16 /mm

FRONT		REAR	
ARM MOUNT	COMPOSITE ☒ ALU ☐ BRASS ☐	ARM SHIM	0 /mm
CHASSIS BRACE	MEDIUM ☐ HARD ☒	CHASSIS	SHORT ☐ MID (KIT) ☒ LONG ☐
SERVO WEIGHT	STANDARD ☒ LOW PROFILE ☐	CHASSIS FLEX	SCREW USED ☒ SCREW NOT USED ☐
		BALANCE	0 g
		BALANCE	45 g